

PAR 20C

Portable floor standing machine

Ratio Range	Available in fixed ratios from 1:1 to 12:1
Viscosity acceptance	Up to 1,500,000 mPa.s
Shot size	11ml up to 108 ml **
Cycle rate	Up to 15 / minute (material dependent)
Reservoir capacity	Directly from 20 lt /25 lt drums



PAR 200C

Fixed floor standing machine

Ratio Range	Available in fixed ratios from 1:1 to 20:1
Viscosity acceptance	Up to 1,500,000 mPa.s
Shot size	11ml up to 194 ml **
Cycle rate	Up to 15 / minute (material dependent)
Reservoir capacity	Directly from 200 lt & 20 lt drums

Rod displacement metering

- Designed for micro-shot dispensing (down to 0.04ml)
- Precise volumetric fixed ratio metering
- Single acting positive displacement
- Adjustable shot volume metering
- Pneumatic or electric drive units
- Disposable static mixing
- Low to medium viscosity acceptance
- Table top or robot mounted



PAR 2P / PAR 2E

Ratio Range	Available in fixed ratios from 1:1 to 18:1
Viscosity acceptance	Up to 500,000 mPa.s
Shot size	0.04 ml up to 7.96 ml **
Cycle rate	Up to 15 / minute
Reservoir capacity	Various options from 0,5 lt up to 20 lt

MIXING NOZZLES AND CARTRIDGES

The full range of disposable static and rotary static mixers are available from stock.



