

Single Magazine Unloader



Application

The **Single Magazine Unloader** is used at the end of the line for unloading of PCB's from the production line. An arriving PCB is taken up by the attached conveyor and then pushed into the magazine by the pusher. The magazine indexes to the next position and is ready for the following unloading cycle.

Features

- Controlled by Omron PLC.
- Easy operation by touch screen.
- Multiple pitches selectable.
- Tower light display for machine status.
- 1 magazine loading capability, discharge magazine from the rear of machine.
- SMEMA interface.
- CE certified.

Specifications

Model	MU-250A-ST	MU-330A-ST	MU-390A-ST	MU-460A-ST
Size	M	L	LL	XL
Power	AC 110/220V \pm 10V, 50/60HZ			
Air Pressure	4 - 6 kgf/cm ²			
Fixed Rail	Front			
PCB Size	350x(50 - 250)mm	460x(50 - 330)mm	535x(50 - 390)mm	535x(50 - 460)mm
Transfer Height	900 \pm 20mm or Specify			
PCB Direction	left to right or right to left(option)			
Magazine Rack Size	350x320x563mm	460x400x563mm	535x460x570mm	535x530x570mm
Pitches	1 - 50, 10mm pitch			
Machine Dimension	1120x1060x1200mm	1280x1220x1200mm	1460x1340x1200mm	1460x1480x1200mm
Machine Weight	200kg	210kg	230kg	250kg

* Other options available on request.

