



Electronic

FLUX-REMOVER (PLUS) EO-RA-007 (+)

Cat.-no. 2916

Latest-generation specialty electronics cleaner for manual cleaning of PCBs and other surfaces.

-Optimized, very fast drying time-

WEEE/RoHS-compliant



Product Description:

FLUX-REMOVER (PLUS) EO-RA-007(+) is a highly efficient, next-generation electronics cleaner. It features a very fast drying time and clean, residue-free performance.

EO-RA-007(+) was specifically developed for manual PCB cleaning of flux residues. This special formulation easily removes most organic residues from soldering and gluing processes, as well as greasy substances, fingerprints, and dust on circuit boards and other surfaces.

EO-RA-007(+) dries extremely quickly and leaves no residue on the cleaned area. The evaporation has been specially optimized so that the contaminants can be easily removed from the circuit board using an ESD wipe. With the specially developed brush attachment, flux or paste residues can be effectively dissolved and removed from all areas of the circuit board.

EO-RA-007(+) is free of PFAS, POPs, benzene compounds, sulfur compounds, halogens, REACH/CLP SVHC substances, as well as acids and alkalis.



EMIL OTTO
Flux- und Oberflächentechnik GmbH
D-65346 Eltville – Eltviller Landstr. 22

Tel.: +49 (0)6123 / 70 46 0 – Fax: +49 (0)6123 / 70 46 15



The above described attributes are average values. They are meant solely for your information and are no specifications as such. These instructions of use are without obligation and do not exempt our customers from their own trials of suitability for their own purposes.

05/2025



Electronic

FLUX-REMOVER (PLUS) EO-RA-007 (+)

Cat.-no. 2916

Latest-generation specialty electronics cleaner for manual cleaning of PCBs and other surfaces.

-Optimized, very fast drying time-

WEEE/RoHS-compliant



Technical data (spray can, compressed gas packaging):

Appearance:	Transparent, clear aerosol
Density at 20 ° C:	<0,7 g/ml
Solvent:	Isopropyl alcohol solvent mixture
Initial boiling point and boiling range:	< -20 ° C (aerosol, gas)
Flash point:	< -20 ° C (aerosol, gas)
Storage (recommendation):	Cool, dry and light protected at 5 ° C - 25 ° C
Free from:	PFAS, POPs, benzene compounds, sulfur compounds, halogens, acids, and alkalis

Technical data (cleaning fluid):

Appearance:	Transparent clear liquid
Density at 20 ° C:	0,7 – 0,8 g/ml
Solvent:	Isopropyl alcohol solvent mixture
Flash point:	1 °C
Storage (recommendation):	Cool, dry and light protected at 5 ° C - 25 ° C.
Free from:	PFAS, POPs, benzene compounds, sulfur compounds, halogens, acids, and alkalis

Advantages of using EO-RA-007(+):

- Ideal for the REWORK
- Easy, fast and accurate removal of flux residue and residue
- Highly efficient cleaning effect
- Short exposure time (short duration of action)
- Very fast drying
- Residue-free
- Gives clean PCBs and solder joints
- Removal of fingerprints on printed circuit boards (PCB)
- High material compatibility
- Economical in consumption

EMIL OTTO
Flux- und Oberflächentechnik GmbH
D-65346 Eltville – Eltviller Landstr. 22
Tel.: +49 (0)6123 / 70 46 0 – Fax: +49 (0)6123 / 70 46 15



The above described attributes are average values. They are meant solely for your information and are no specifications as such. These instructions of use are without obligation and do not exempt our customers from their own trials of suitability for their own purposes.



Electronic

FLUX-REMOVER (PLUS) EO-RA-007 (+)

Cat.-no. 2916

Latest-generation specialty electronics cleaner for manual cleaning of PCBs and other surfaces.

-Optimized, very fast drying time-

WEEE/RoHS-compliant



Standard packing units (domestic):

- Spray can with 400ml
- Canisters (jerry cans 3H1) with 5 l to 30 l content
- Other packaging sizes on request

Safety (Occupational Safety / Environment / Transport):

Additional information on the ingredients (hazardous substances), safe handling, storage, transport and disposal can be found in the current safety data sheet (SDS, SDS, MSDS).

EMIL OTTO
Flux- und Oberflächentechnik GmbH
D-65346 Eltville – Eltviller Landstr. 22

Tel.: +49 (0)6123 / 70 46 0 – Fax: +49 (0)6123 / 70 46 15



The above described attributes are average values. They are meant solely for your information and are no specifications as such. These instructions of use are without obligation and do not exempt our customers from their own trials of suitability for their own purposes.

05/2025